CAMERA

ISN-9440S5L-C

4MP Dual Illumination Water-proof Bullet Network Camera

- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution: 4MP (2560 × 1440)
- Auto day/night switch
- 3D DNR, WDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- 10~20m white light view distance; 20~30m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support dual streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support line crossing detection & region intrusion detection
- Support SMD
- Support P2P function
- Support dual-system backup



RoHS CE FC PoE ONVIF

en.tvt.net.cn

For more information, please visit our website

Asya Telekomünikasyon ve Netgüvenlik Sistemleri

Merkez: Adres: Mehmet Akif Mahallesi, Öztekin caddesi, No:18 Asya Plaza Ümraniye / İSTANBUL

Perpa Şube: Adres: Perpa Ticaret Merkezi B Blok Kat:8, No:908 Okmeydanı / İSTANBUL

Tel: +90(850) 433 27 92

Web site: www.isee.com.tr

E-mail: info@isee.com.tr

SPECIFICATIONS

Specifications \ Model	TD-9440S5L-C
Camera	
Image Sensor	1 / 3 "CMOS
Image Size	2560×1440
Electronic Shutter	1 / 3s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.014 lux @F2.0, AGC ON; 0 lux (Illumination on)
Lens	2.8mm@F2.0, Horizontal FoV: 95°;Vertical FoV:53°;Diagonal FoV:111° 3.6mm@F2.0, Horizontal FoV:73°;Vertical FoV:40°;Diagonal FoV:88°
Focus Lens Mount	Fixed
Day&Night Wide	M12
Dynamic Range	ICR
BLC	Digital WDR
	Yes
HLC	Yes
Defog	Yes
Digital NR	Yes
S/N Ratio	≥50dB
Angle Adjustment	Pan: 0°~360°; Tilt:0°~80°;Rotation: 0°~360°
DORI Distance	

Lens	Detect	Observe	Recognize	Identify
2.8mm	58m(190ft	23m(76ft)	12m(38ft)	6m(19ft)
3.6mm	)	32m(104ft)	16m(52ft)	8m(26ft)

Image	79m(260ft
Video Compression	)Main stream: H.265+ / H.265 / H.264 + / H.264 Sub stream: H.265+ / H.265 / H.264 + / H.264 / MJPEG
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, 640× 360, VGA (640× 480), 480× 240, CIF
Main Stream	4MP/3MP/1080P/720P (60Hz: 1~30fps; 50Hz: 1~25fps)
Sub Stream	D1/640×360/VGA/480× 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	32 Kbps ~ 4 Mbps
Audio Compression	G711A/U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, Flip horizontally/vertically, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45 (10/100 Base-T)
Video Output	No
Audio	1CH built-in MIC
Storage	No
Reset Functions	No
Remote Monitoring	
	Web browser /TVT NVR/NVMS2.X/Mobile APP
Web Browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, DDNS, 802.1x, HTTP, QoS, P2P
Interface Protocol	ONVIF
API&SDK	Yes
Storage	Network remote storage
Motion Detection	Support smart motion detection; filtering motion alarm triggered by other target types except people.
Smart Alarm	White light alarm triggered by smart events, IP conflict, network disconnected
Smart Event	(People) region intrusion/line crossing detection
General Function	Watermark, video mask, heartbeat, one-click disarming
Security	Video encryption, firmware encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP

PoE	Yes, IEEE802.3af
Supplement Light Range	IR range: 20 ~ 30 m; white light range:10 ~ 20 m
Ingress Protection	IP67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 5.5W
Operating Environment	- 20 °C ~ 55 °C (-4°F~131°F); Humidity: less than 95 % (non-condensing)
Storage Environment	- 20 °C ~ 60°C (-4°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	162.1 × 74.8 × 73.8
Weight (net)	Approx. 0.25KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE ACCESSORIES

TD-YXH0301

TD-YXH0103


TD-YXH0104

TD-YXH0301+ TD-YZJ0501

TD-YXH0301+ TD-YZJ0601

TD-YXH0301+ TD-YZJ0810

AVAILABLE MODEL

Available Model	TD-9440S5L-C(D/PE/AW2)