


ISN-9422S4-C

2MP Dual Illumination Water-proof Bullet Network Camera



- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution: 2MP (1920 × 1080)
- Auto day/night switch
- 3D DNR, HWDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- 30~40m white light view distance; 30~50m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support P2P function
- Support SMD
- Support line crossing detection, region intrusion detection, abandoned/missing object detection, video exception detection




SPECIFICATIONS

Model	TD-9422S4-C	
Specifications		
Camera		
Image Sensor	1 / 2.8 "CMOS	
Image Size	1920×1080	
Electronic Shutter	1/3s ~ 1 / 100000s	
Iris Type	Fixed Iris	
Min. Illumination	0.008 lux @F1.6, AGC ON; 0 lux with illumination on 0.006 lux @F1.4, AGC ON; 0 lux with illumination on	
Lens	2.8mm@F1.6, H.FoV:107°; V.FoV: 56°; D.FoV:126° 3.6mm@F1.6, H.FoV: 89°; V.FoV: 47.5°; D.FoV:104° 6mm@F1.6, H.FoV: 53.8°; V.FoV: 29.3°; D.FoV:62.8°	2.8~ 12mm@F1.4 H.FoV: 101.9°~33°; V.FoV: 54.3°~19°; D.FoV: 124.7°~ 39°
Focus Lens Mount	Fixed	Varifocal (manual)
Wide Dynamic Range	M12	Ø 14
Range	120dB	
BLC	Yes	
HLC	Yes	
Digital NR	Yes	
S/N Ratio	≥50dB	
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°;Rotation: 0°~360°	
Image		
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub/Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG	
H.265 Compression Standard	Main Profile@Leve4.1 High Tier	
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, VGA (640× 480), 480× 240, CIF	
Main Stream	1080P/720P (60Hz: 1~30fps; 50Hz: 1~25fps)	
Sub Stream	D1/VGA/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)	
Third Stream	D1/480× 240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)	
Bit Rate	64 Kbps ~ 6 Mbps	
Bit Rate Type	VBR / CBR	
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser	
Audio Compression	G711A/U	
ROI	Each ROI to be configured separately	
Interfaces		
Network	RJ45	
Video Output	No	
Audio	1CH audio input; 1CH built-in MIC	
Storage	Built-in micro SD card slot, up to 256GB	
Reset	Yes	
Functions		
Remote Monitoring	Web browser /TVT NVR/NVMS2.X/Mobile APP	
Web Browser	Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+	
Online Connection	Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission	
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, HTTP POST, P2P, QoS ONVIF	
Interface Protocol	Network remote storage; micro SD card storage	
Storage	Motion detection, SMD, SD card error, SD card full, IP address conflict, network disconnection, video exception	
Smart Alarm	Line crossing/region intrusion (human/vehicle classification), abandoned/missing object detection	
Smart Event	Watermark, IP address filtering, video mask, heartbeat, ANR, cloud upgrade, smart supplement light, corridor pattern	
General Function	Yes (IEEE802.3af)	
PoE		
Supplement Light Range	IR range: 30 ~ 50 m; white light range:30 ~ 40 m	
Ingress Protection	IP67	
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP	

DORI Distance				
Lens 2.8mm 3.6mm	Detect	Observe	Recognize	Identify
6mm 2.8~12mm(W)	41m(133ft)	16m(53ft)	8m(27ft)	4m(13ft)
2.8~12mm(T)	50m(163ft)	20m(65ft)	10m(33ft))
Others	83m(271ft)	33m(108ft)	17m(54ft)	8m(27ft)
Power Supply	43m(142ft)	17m(56ft)	9m(28ft)	4m(14ft)
Power Consumption	132m(433ft)	53m(173ft)	26m(86ft)	13m(43ft)
Storage Conditions				
Operating Conditions	DC12V/PoE			
Dimensions (mm)	< 8W			
Weight (net)	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)			
Installation	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)			
Certificate	217.8 × 80.5 × 80.3			
	Approx. 0.68KG			
	Ceiling mounting; wall mounting			
	CE, FCC			
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)			

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-9422S4-C(D/PE/AW3)	Fixed lens
	TD-9422S4-C(D/FZ/PE/AW3)	Manual zoom lens